



| Art.nr | El.nummer | Farge | RAL |
|--------|-----------|-----------|------|
| 1741AL | 3102462 | ALUMINIUM | 9006 |
| 1741GR | 3102463 | GRAFITT | 7016 |
| 1741W | 3102464 | HVIT | 9003 |

Generell informasjon

| | |
|-----------------------------------|------------------------------|
| Type armatur | |
| Materiale | Pulver lakkert aluminiumstøp |
| Avdeknings materiale/optikk | Glass - herdet, klar |
| Type lyskilde | GU10 |
| Lysstyring | Dimbar (Triac) |
| Effekt W | 3,9W |
| Armatureffekt | 3,9W |
| Modul lumen | 265lm |
| Lumen ut | 210lm |
| Modul effektivitet | 67,9lm/W |
| Armatur Lumen/Watt | 53,8lm/W |
| ULOR | 0% |
| Fargetemperatur | 2700K |
| Farvekonsistens (McAdam-Ellipse) | SDCM3 |
| Fargegjengivelsesindeks | 90 |
| Beregnet levetid L70/B50 ved 25°C | 40 000h |
| Energieffektivitetsindeks (EEL) | A+ |
| Virkningsgrad | PF > 0,8 |
| Ta nominel: | +25°C |

Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual

