




SPECIFICATION		DATA	
Material and thickness	Cold roll steel 0.8mm	System power	18W
Diffuser Material	Total Lumen	1994LM
Reflector/purity	System efficiency	110.8LM/W
Cross plates Quantity V	0	UGR	<22
Frame Material/color	Aluminium/White	Beam angle	129.3
Certificates	CE RoHS EN62471	Driver brand
Class	I	Dimmable	AVAILABLE
IP	IP44	PF	>0.96
Warranty	5 YEARS	THD	<20%
IK	IK05(0.7J)	Flicker free	<10%
Glow wires	LED Chip brand	GE AC
Connector	LED PCB board	1PCS
Cut out hole	CRI	>80
External size	LM80 8000 hours	97.9(55degrees)
Weight	1.68KGS	L70/B50 hours	YES
Size	1250x45x100mm	IES file available	YES
Box Quantity packaging size	128x38x30cm 10pcs	LM79	YES
Quantity for 40"HighCube	5000pcs	Low Color Tolerance	ANSI/MacAdam 3
		DC Voltage range	27~54V


NEPTUN BENKARMATUR LED
18W M/STIKK

 This luminaire contains built-in LED lamps.

 LED

The LED lamps cannot be changed in the luminaire

874/2012 



H[m]	D[m]	Max lux	Med lux	Beta=129.3°	G=0.0 Max not at G
1.00	3.37	141	28		
2.00	6.74	35	7		
3.00	10.10	16	3		
4.00	13.47	9	2		
5.00	16.84	6	1		

