



Art.nr	El.nummer	Farge	RAL
1260GA	3120023	GALVANISERT STÅL	-
1260B	3120024	SORT	9005

## Generell informasjon

Type armatur	
Materiale	Galvanisert stål
Avdeknings materiale/optikk	PMMA, opal
Type lyskilde	LED modul AC
Lysstyring	Dimbar (Triac)
Netto / Brutto vekt armatur	7,3kg / 7,3kg
Forpakkingsstørrelse [cm]	21x21,5x5,7
LED	Lumens EDC/47C/10W/830/230V/A
Effekt W	10W
Armatureffekt	10W
Modul lumen	900lm
Lumen ut	294lm
Modul effektivitet	90lm/W
Armatur Lumen/Watt	29,4lm/W
Fargetemperatur	3000K
Farvekonsistens (McAdam-Ellipse)	SDCM3
Fargegjengivelsesindeks	80
Beregnet levetid L70/B50 ved 25°C	50 000h
Energieffektivitetsindeks (EEL)	<b>A+</b>
Virkningsgrad	PF > 0,99
Ta nominal:	+25°C
Inrush current	46,1mA/500µs
Antall armaturer på automatsikring	<b>B 10A: 42, B 16A: 68, C 10A: 70, C 16A: 115</b>

## Filer som kan lastes ned

Photometric LDT files, Photometric IES files, Manual